



# CAPTAIN

**DFAC**

*Setting Sail, Delivering Dreams*

## CAPTAIN-C

*GVW 7,500kg* **6-Wheeler**

## CAPTAIN-E

*GVW 5,000kg* **4-Wheeler**



*All Pictures shown are for illustration purpose only.*



# DONGFENG

**DFAC**



**5 -Year Warranty**  
Or 300,000 km  
whichever comes first

# TECHNICAL SPECIFICATION

Model		CAPTAIN E	CAPTAIN C
Chassis Details	Model Code	EM98-101J	CA9R-301J
	G.V.W (Gross Vehicle Weight)	5000kg	7500kg
	Cab Width	1880mm	2030mm
	Maximum Speed	100km/h	100km/h
	Gradeability	31%	51%
	Curb Weight	1730kg	2790kg
	Turning Radius	7.5m	8.0m
Engine	Model	JE493ZLQ4	Cummins ISF3.8s4R154
	Type	Diesel, in-line 4-cylinder, Turbo Intercooler	
	Fuel Injection System	ECU Control Common Rail Injection	
	Displacement (cc)	2771	3760
	Max. Output (kW/PS@rpm)	80 / 108 @ 3400	115 / 156 @ 2600
	Max. Torque (N.m@rpm)	260 @ 2,000	500 @ 1200
	Emission Standards	Euro IV	
Clutch	Emission Control	EGR + DOC + POC	
	Form	Diaphragm Spring	
	Diameter	Φ265mm	Φ350mm
Gearbox	Type	5 Speed MT	6 Speed MT
	Model	WLY-5GT32	FAST-C6J55T
	Gear Ratio	1 <sup>st</sup>	6.18
		2 <sup>nd</sup>	3.33
		3 <sup>rd</sup>	2.08
		4 <sup>th</sup>	1.39
		5 <sup>th</sup>	1.00
		6 <sup>th</sup>	0.78
	Reverse	4.505	5.57
	Final	4.875	4.33
Frame	Cross-sectional Dimensions(mm)	190 x 55 x 4.5	192 x 65 x 6
	Width (mm)	760	800
	Layer	Single Layer	
Braking	Service Braking system	Dual-circuit hydraulic brakes with vacuum assist.	Dual-circuit Air brakes
	Front / Rear	Drum / Drum	
	Auxiliary Brake system	Exhaust Brake	
	Parking Brake	Mechanical internal-expanding, acting on transmission output shaft	Mechanical internal-expanding, acting on rear wheels
Axle	Front	Type	Reversed Elliot, I-Beam
		Capacity	2,700kg
		Maker	BANGLE
	Rear	Type	Full Floating, Pressed welding housing, Hypoid Gear
		Capacity	3,500kg
		Maker	BANGLE
Suspension	Front	Type	Multi Leaf Spring with Dual Acting Shock Absorber
		Number of Springs	6
	Rear	Type	Multi Leaf Spring, Dual Acting Shock Absorber and Stabilizer Bar
		Number of Springs	6 + 5
Tyre	Wheel Type	6 Stud Tubeless Tires	
	Wheel Size	7.00R16-14PR	215/75R17.5
	Rim Size	5.50F-16 Steel	6.00 x 17.5 Steel
	Number of Tires	4 + 1	6 + 1
Cab	Tilting	Mechanical Type	
	Steering	Recirculating ball with Hydraulic power assistance	
Safety Features	ABS + ESC	Yes	
	Reverse Sensor	Yes	
Electrical	Battery	12V, 100AH	12V, 100AH x 2pcs
	Alternator	14V - 80A	28V - 70A
Fuel Tank Capacity		76L (Steel)	120L (Aluminium)
Chassis Dimension (mm)	Overall Length (OL)	4785	6750
	Overall Width (OW)	1930	2110
	Overall Height (OH)	2200	2360
	Wheelbase (WB)	2515	3800
	Front Overhang (FOH)	1045	1145
	Rear Overhang (ROH)	1225	1805
	Front Tread (FT)	1613	1745
	Rear Tread (RT)	1540	1612

Disclaimer: The Manufacturer reserves the right to make changes to technical parameters & designs or to discontinue models without prior notice.

## DONGFENG COMMERCIAL VEHICLE (MALAYSIA) SDN BHD


A Member of Sunway Group

Lot 526, Persiaran Subang Permai, Sungai Penaga Industrial Park,  
USJ 1, 47600 Subang Jaya, Selangor Darul Ehsan.

Tel: 03-8021 9068 Fax: 03-8021 9069

Website: <http://dongfeng.my/>

Authorised Dealership



**SUNWAY®**  
TRADING &  
MANUFACTURING

© Version 11/2023